



The LCD Keypad is an extension module for the Terxon SX and Terxon MX. Installed near the entrance door, it allows you to quickly operate your alarm panel. The LCD keypad is connected to the Terxon SX/MX via a 4-wire bus cable. Up to 4 control units can be integrated into the alarm system. Arranged in various parts of your building, these extension modules provide additional convenience. The system can be conveniently activated or deactivated via any keypad using a PIN code and proximity chip key. The status of the alarm control panel is also displayed on the plain text display of the control unit. You can conveniently view and, of course, change system settings, programming and the 250x event memory of the Terxon S/M. The LCD keypad is designed in an elegant white color. Thus, it is not only an enhancement for each entrance area, but it is also optically in line with the wireless components of the Secvest 2WAY.

Technologies

- For operating and programming the alarm panel Terxon SX/MX
- Suitable for indoor and protected outdoor use
- Operate your alarm panel with PIN code or proximity key fob
- Proximity chip reader integrated

Technical data - 4043158015713

Connections	4-core bus, screw terminal for additional tamper contact, panic alarm button, and button for manually ending the exit delay
DC voltage supply	12 V
Depth	30 mm
Dimensions	(WxHxD) 135x135x30 mm
Display	alphanumeric LCD-Display 2lines
Environmental class	II
Height	135 mm
Housing material	ABS

4043158015713

Art.-Nr. AZ4110

Seite 2 von 2

Technical data - 4043158015713

IP protection class	54
Installation location	Indoors and protected outdoor areas
Integrated siren	1
Length	30 mm
Max. humidity	94 %
Max. operating temperature	55 °C
Min. operating temperature	-10 °C
Net weight	0,2 kg
Power consumption	30 mA
Sabotage monitoring	Yes
Security level	2
Width	135 mm