



#### COMPACT 4 MPX 24/7 SURVEILLANCE CAMERA

As a full-colour day/night camera, the IP spherical dome delivers the best surveillance images in 4 MPx resolution. The weatherproof IP67 housing is designed for outdoor use. External white light LEDs provide clear images day and night. The camera can be accessed from the mobile app at any time.

#### Top surveillance in the dark

Clear colour images in total darkness thanks to full-colour day/night technology - rich in detail for solid evidence. The slightest residual light is effectively amplified by the special lens and the extra light-sensitive image sensor, while the white light LEDs provide the sensor with a touch of extra light.

#### Best overview

The IP dome overlooks a horiz. field of view of 108° or 95° (variant A or B).

#### Autom. Object recognition

The security camera distinguishes relevant movements (people, vehicles) from interferences (branches, light, etc.) - and minimises unnecessary motion alarms.

#### Recording and compatibility

Recording is done on ABUS recorders, VMS/software or local microSD card. The camera is compatible with ABUS Secvest, Secoris and wAppLoxx Pro.

#### Easy installation

The camera is mounted on the ceiling or wall (wall bracket/ insta. box available). The free 'ABUS IP Installer' software is available for integration into the network.

Notes: Without power supply unit, because PoE.  
 The effective LED range varies depending on the location.

### Technologies

- 4 MPx resolution (2,688 x 1,520 @ 25 fps) for crisp surveillance images
- 2.8 mm fixed-focus lens for a good overview (108° field of view)
- Detailed, highly usable colour images in the dark thanks to full-colour day/night technology; effectively amplifies even minimal ambient light using a special lens and very light-sensitive image sensor
- Discreet illumination of the field of view with white-light LEDs (up to 30 m range) for accurate colour images in total darkness (e.g. indoors); touch of illumination for the light-sensitive image sensor (barely visible to the human eye)
- Object recognition (human & vehicle): Video content analysis with fully automatic differentiation between people/vehicles and interferences (branches, light, etc.)
- Optional output of 3 video streams in ideal resolution for, e.g., live image, recording, mobile access, etc.
- Robust, weatherproof housing (IP67) with external WL-LEDs for clear image results without disturbing reflections in the glass dome
- Supports H.264, H.265, MJPEG (incl. Dynamic GOP)
- microSD card slot for internal data storage, encrypted for high data security (optional)
- 12 V DC & PoE (802.3af)

### Technical data - 4043158193640

Additional functions	White light range up to 30 m
Alarming	E-Mail, NAS, FTP
Aperture at minimum illumination (colour)	F1.0
Audio	Integrated: Microphone
Backlight compensation	WDR, BLC, HLC
Camera type	Dome
Compatible with	ABUS NVR/DVR, ABUS Link Station App, Synology Surveillance Station 6.0.1+
Compatible with ABUS Link Station	Yes
Compatible with Comfion	Yes
Compatible with Secoris	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC
DC voltage supply	12 (+/-25 %) V

# 4043158193640



Security Tech Germany

Art.-Nr. IPCS54511A

Seite 3 von 4

## Technical data - 4043158193640

Design	Dome
Digital zoom	Yes
Dimensions	(LxBxH) 139x139x128 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/1000000 s
Encryption	HTTPS, TLS 1.1/1.2
Focal length	2,8 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Functions	Scene Change Detection, Region of Interest
Gross weight	0,7 kg
Height	128 mm
Horizontal viewing angle	108 °
Housing material	Metal
IP protection class	67
Image enhancement	WDR, BLC, HLC, 3D DNR, Vertical Display (not in Smart-Event mode)
Image integration	Yes
Image sensor	1/1.8" Progressive Scan CMOS
Installation type	Ceiling, Wall
LAN network access	RJ45 10M/100M self-adaptive
Language of instructions	DE, UK, FR, NL, DK
Length	139 mm
Lens	Fix
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	2688 x 1520 @ 30 fps
Microphone	Yes
Min. operating temperature	-25 °C
Minimum illumination (colour)	0,0005 lx
Motion detection	8 zones
Net weight	1 kg
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server, P2P, QoS, 802.1X, IGMP, Bonjour, PPPoE, SNMP
Noise reduction	3D DNR
Number of streams	3
Number of users	32
OSD language	DE, UK, FR, NL, DK, IT
Other functions	Object Classification Person/Vehicle
Pixels (effective)	2688(H) x 1520(V) pixel

**Technical data - 4043158193640**

PoE standard	IEEE 802.3af
Power consumption	600 mA
Private zones	4
Resolution	4 MP
Resolution modes	Stream 1: 2688 x 1520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1920 x 1080 @ 10 fps
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE11, Mozilla Firefox, Google Chrome, MS Edge
Technology	IP
Vertical viewing angle	55 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection, Region Entrance, Region Exit
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265
Video network bandwidth	32 kBit/s - 8 MBit/s
White balance	AWB, Manual
White-light LEDs	2
White-light range (up to)	30 m
Width	139 mm