



CENTRAL UNIT

NETWEIGHT	610 g
DIMENSIONS	127 x 35 x 90 mm
COLOUR	Grey
PACKAGING	<ul style="list-style-type: none"> • Ecological cardboard box (approx. 16 x 17 x 4.5) • Self adhesive seal • Serial number
SCOPE OF DELIVERY	<ul style="list-style-type: none"> • 9001 IoTect Central Unit • SmartX™ Keycard approx. 85.6 x 53.98 x 0.76 mm) for secure and clear identification of the lock owner • Charger cable and adaptor • User guide • Keycard fixture
IP PROTECTION CLASS	IP54 (in combination with form factor use)
TEMPERATURE RANGE	-20 C up to +40 C

CONNECTIVITY

GSM MODULE	GSM/GPRS uBlox Modul
GSM TRANSMISSION POWER	1 W
SIM CHIP	permanently installed SIM Chip
FREQUENCY RANGE	890 – 915 MHz and 935 – 960 MHz (GSM 900) 1.710 – 1.785 and 1.805 – 1.880 MHz (GSM 1800)

BLUETOOTH® MODULE	Yes
BLUETOOTH® STANDARD	ABUS SmartX™ (BLE 4.1)
BLUETOOTH® TRANSMISSION POWER	<10 mW
ENERGY	
BATTERY	Rechargeable Lithium Ion Polymer battery , 3.6 V; 750 mAh
ADAPTOR	Input: 100 240V ~, 50/60 Hz, 0,6A Max Class II, IP20. Output: 5Vdc, 1A
CHARGING SOCKET	USB-C DIN EN 60529 IP X8
FUNCTIONS	
GPS MODULE	uBlox Modul
MICROCONTROLLER	EFM
ACCELERATION SENSOR	3 axes
SIGNALLING FUNCTION	<ul style="list-style-type: none">• RGB LED for status report (e.g. blue while establishing bluetooth connection)• Acoustic alarm up to 100 dB (in ideal conditions and immediate proximity of the speakers)• acoustic signalling for status changes (e.g. confirmation of activated monitoring mode)



FORM FACTOR

SHACKLE 12 MM

- 165 g
- 12 mm diameter
- Case hardening steel

SHACKLE 8 MM

- 115 g
- 8 mm diameter
- Stainless steel

CHAIN

- 1.100 g
- High quality fabric sleeve
- 6 mm square chain
- Hardened steel