

Secvest Wireless Remote Control

Art.-Nr. FUBE50015

Seite 1 von 2



Convenient operation of the alarm control panel

The bi-directional wireless remote control is a practical accessory for controlling Secvest wireless alarm systems at the touch of a button. It also allows the current system configuration status to be viewed at any time. The FUBE50015 remote control is compatible with Secvest, Secvest IP and Secvest 2 WAY wireless alarm units.

Reliable arming at long range

The remote control enables convenient arming and disarming of the alarm system from a distance. Thanks to eight integrated LEDs, real-time feedback is provided regarding changes to the system status. The transmission range is approx. 30 metres.

Rapid assistance in an emergency

Simultaneously pressing the 'arm' and 'disarm' buttons triggers a panic alarm. This ensures the health and safety of residents as well as protecting your possessions.

Display of additional information

By pressing the third button, important information about the status of the alarm control panel can be queried (armed, disarmed, internal protection active, fault). Feedback appears on the remote control immediately.

Useful convenience functions

The fourth button is fully programmable. Along with arming the alarms for the interior, it can also be used to activate an output (e.g. to control a garage door). This button can be programmed directly on the alarm control panel.

Secure wireless communication

Thanks to a secure wireless communication procedure, this product is protected against 'replay attacks', as are the Secvest wireless alarm system and Secvest Touch alarm systems. This procedure for preventing third party tampering exceeds the requirements of the "DIN EN 50131-1 level 2" security standard.

Technologies

- User-friendly remote control with easily identifiable key symbols
- For use with Secvest, Secvest IP and Secvest 2 WAY wireless alarm systems

Secvest Wireless Remote Control

Art.-Nr. FUBE50015

Seite 2 von 2

- Features 'arm', 'disarm' and 'status query' keys
- 8 LEDs provide an overview and display current system status
- Button for custom configuration available (Secvest wireless alarm system only)
- Communicates with the Secvest and Secvest Touch via a secure wireless connection

Technical data - Secvest Wireless Remote Control

Battery - max. battery life	2 y
Battery - type	CR2450 3V Li-Mn (FU2987)
DC voltage supply	3 V
Depth	62 mm
Dimensions	(WxHxD) 36 x 17 x 62 mm
Display	LED
Environmental class	II
Height	17 mm
Housing material	ABS
Language of instructions	DE, UK, FR, NL, DK, ES
Length	62 mm
Max. humidity	75 %
Max. operating temperature	40 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	200 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	200 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,035 kg
PSTI conformity required	No
Radio frequency	868,6625 MHz
Radio power	10 mW
Security level	2
Voltage monitoring	Yes
Width	36 mm