

ABUS Wi-Fi Battery Cam

Art.-Nr. PPIC90520X

Seite 1 von 2



Technical data - ABUS Wi-Fi Battery Cam

Alarming	Push notification
Audio bitrate	64kbps
Audio compression	g711
Audio input	Microphone
Audio output	Loudspeaker
Battery type	2 x 18650 Li-Ion rechargeable batteries
Colour	Black / White
Colour temperature	3000 K
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
DC voltage supply	5 V
DSP	Ingenic T30
Day/night switching	Auto
Dimensions	103 x 51 x 54 mm
Encryption	WPA2
Focal length	2,9 mm
Frequency range	2,4 GHz
Gross weight	0,277 kg
Horizontal viewing angle	115 °
Housing material	Plastic
IP protection class	65
Image sensor	Sony IMX307
LED white light brightness	28 lm
Lens mount	5G
Max. humidity	90 %
Max. operating temperature	50 °C
Max. resolution @ frame rate	Full HD (1080p) @ 15fps
Microphone	Yes
Min. humidity	10%

ABUS Wi-Fi Battery Cam

Art.-Nr. PPIC90520X

Seite 2 von 2

Technical data - ABUS Wi-Fi Battery Cam

Min. operating temperature	-20 °C
Minimum illumination (colour)	1 lx
Network protocols	802.11 b/g/n
Number of users	3
PIR range	8 m
PIR viewing angle	112 °
Plug type	microUSB
Rechargeable battery	Yes
Rechargeable battery running time	up to 6 months (depending on local conditions)
Recording modes	PIR motion detection / Manual
Resolution modes	VGA / 720p / 1080p
Simultaneous network access	3
Software	App: ABUS App2Cam Plus (Android/iOS)
Storage medium	Micro SD Card, up to 128G
Technology	IP
Vertical viewing angle	75 °
Video compression	H.264
WLAN network access	Wi-Fi (2,4GHz)
White balance	AWB
White-light LEDs	1
Wireless range	10-30 metre, depending on local conditions m