


FGI7600N (700-1050 mm x 600 mm)

Seite 1 von 2



SECURING DIRECT ROUTES

Window grills to protect basement and ground floor windows from attempted break-ins.

Time and again, the direct route is enough for criminals to break into your home. Basement and ground floor windows, if insufficiently protected, make it easy for them to do so. Secure these windows with a reliable grill. The width of the window grill can be flexibly adjusted to the window in question. Vertical mounting or the combination of two grilles on top of each other is also possible without any problems. The material used is particularly weather-resistant. Corrosion resistance can be increased even further by using metal protective lacquers.

Technologies

- For mounting in the window soffit
- Including safety screws and dowels
- Finishing: thick-layer passivated, used in the
- An additional sealing can further increase corrosion resistance

Operation and use

- Protection of basement and ground floor windows
- Width adjustable window grills

Technical data - FGI7600N (700-1050 mm x 600 mm)

Weight	6500 g
Window type	Basement window
colour	silver
recommended for window reveal width	700-1050 mm
type of cylinder	Pressure cylinder

FGI7600N (700-1050 mm x 600 mm)



Security Tech Germany

Seite 2 von 2

Technical data - FGI7600N (700-1050 mm x 600 mm)

EAN	4003318963742
-----	---------------

Technical drawing

