

Base station ABUS Battery Cam Pro

Art.-Nr. PPIC91000X

Seite 1 von 1

Technical data - Base station ABUS Battery Cam Pro

Alarming	Push notification / E-Mail
Audio compression	PCM
Audio output	Built-in Speaker
Base event	PIR person detection / PIR motion detection / Manual
Colour	white
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
DC voltage supply	12 V
Dimensions	150 x 110 x 25 mm
Encryption	AES 128bit, WPA/WPA2-PSK
Frame rate	15
Frequency range	2,4 GHz
Housing material	plastic
Loudspeaker	85dB @ 10cm
Max. humidity	90 %
Max. operating temperature	40 °C
Max. resolution @ frame rate	3 MP @ 15 fps
Min. humidity	0,1
Min. operating temperature	-10 °C
Number of channels	4
Number of users	3
Power consumption	180 mA
Private zones	3
Recording modes	max. 3 MP
Resolution modes	VGA / 720p / 1080p / 3 MP
Storage medium	USB flash drive (up to 128 GB)
Technology	Network
Total video channels	4
Video Content Analysis (VCA)	Person detection
Video compression	H.264
Video output	VGA / 720p / 1080p / 3 MP