

# EasyLook pan/tilt camera

Art.-Nr. PPDF17620X

Seite 1 von 2

## Technical data - EasyLook pan/tilt camera

Area of application	Outdoor use
Base event	Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000; PPDF17100
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
DC voltage supply	12 V
Day/night switching	Auto
Dimensions	210 x 120 x 160 mm
Encryption	WPA2
Focal length	4,1 mm
Frequency range	2,403 - 2,478 GHz
Functions	Night vision, Zoom, Intercom (2-way audio), People recognition
Horizontal viewing angle	85 °
Housing material	Plastic
IP protection class	66
IR LEDs	Yes
IR range (up to)	15 m
Image sensor	1/3" CMOS
Loudspeaker	Yes
Max. humidity	90 %
Max. operating temperature	50 °C
Max. resolution @ frame rate	2304 x 1296 @15fps
Microphone	Yes
Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0,1 lx
Minimum illumination (colour)	1 lx
Net weight	0,687 kg
Optical Wave Length	940 nm
Pan/tilt range	270° / 90°
Plug type	DC-plug: 5,5 x 2,0 mm
Power consumption	3,75 W
Power supply	Power adapter

# EasyLook pan/tilt camera

Art.-Nr. PPDF17620X

Seite 2 von 2

---

## Technical data - EasyLook pan/tilt camera

Private zones	4
Resolution modes	2304 x 1296 (3MP)
Sensitivity	-88 dBm
System	Stand-alone
Technology	Wireless
Transmission power	20 dBm
Vertical viewing angle	45 °
Video bit rate	2Mbps
Video compression	H.264+
White balance	Auto
Wireless range	(Depending on installation) 20 - 50 m