

2-wire distributor for video module

Art.-Nr. TVHS21310

Seite 1 von 2



TOTAL MODULAR: THE VIDEO INTERCOM SYSTEM

See people in front of the door, talk to them, open the door. Easy to install, modular and adaptable to any building - with 2-wire technology or via IP network.

Perfect 2-wire installation

The 2-wire distributor (distributor, converter unit) establishes communication between the 2-wire video module TVHS21010 and the 2-wire touch monitor (indoor station) TVHS21210. The distributor is a necessary component for the installation of the ModuVis door intercom system with 2-wire technology.

Totally modular, extensively expandable

A clear advantage: If the basic configuration with video module, indoor station (touch monitor) and 2-wire distributor (necessary for 2-wire installation) is set, additional modules and monitors are simply added to the system depending on the number of flats and local requirements. In this way, up to 49 rings are possible - and one monitor is integrated for each party. Whichever variant of video module and monitor (2-wire or IP/PoE/WLAN) is chosen - the systems are compatible with each other.

Technologies

- 2-wire distributor for the ModuVis door intercom system
- Required for installation with 2-wire video module and 2-wire indoor station

Technical data - 2-wire distributor for video module

Connections	1 x DC, 8 x Bus I/O
DC voltage supply	24 V
Dimensions	144 x 90 x 65 mm
Height	90 mm
Length	65 mm
PSTI conformity required	No

2-wire distributor for video module

Art.-Nr. TVHS21310

Seite 2 von 2

Technical data - 2-wire distributor for video module

Power consumption	2.500 mA
Width	144 mm