## Comfion wireless smoke alarm



Art.-Nr. FURM80000 Seite 1 von 3



#### Reliable lifesaver

This compact and powerful wireless smoke detector adds reliable smoke detection to the Comfion security system and provides extra safety. In the event of a fire alarm, an 85 dB warning tone sounds and you are also informed directly via the Comfion app.

### Safety through reliable smoke detection

Simple integration into the existing system means that dangerous smoke developments are recognised at an early stage and an alarm is triggered - whether in presence or absence. With a compact housing and a weight of only 95g (incl. battery), the detector can be flexibly positioned on the ceiling. Thanks to its status LED, the current operating status of the device is displayed. The detector operates at a radio frequency of 868 MHz. The detector communicates with the Comfion alarm panel via radio signal.

#### 5-year battery lifetime

The smoke detector is powered by a long-life CR123A battery, which has a lifetime of up to 5 years. The detector is

# Comfion wireless smoke alarm



Art.-Nr. FURM80000 Seite 2 von 3

suitable for rooms up to 50m² in size, making it ideal for use in living spaces and small offices. The battery is easy to replace.

### **Technologies**

- Comfion extension for smoke detection
- Button for manual self-test and test alarm
- Compact design (30 x 86 mm) and lightweight (95 g)
- Suitable for rooms up to 50m<sup>2</sup>
- Long-life battery (5 years)
- Temperature range 0°C to 40°C

#### Technical data - Comfion wireless smoke alarm

Battery - max. battery life	5 y
Battery - quantity	1
Battery - type	CR123A / CR17335
Certifications	EN 14604:2005 + AC:2008
Compatible with	Comfion
DC voltage supply	3 V
Depth	30 mm
Detector coverage area (m2)	50 m <sup>2</sup>
Diameter	86 mm
Dimensions	30 x 86 mm
Environmental class	
Gross weight	0,095 kg
Max. humidity	85 %
Max. operating temperature	40 °C
Max. receiving range (free	400 m
field)	
Max. transmission range (free	400 m
field)	
Min. operating temperature	0 °C
Modulation	2FSK
Net weight	0,08 kg
Radio frequency	868 MHz
Radio power	25 mW
Status display	Yes
Type of detection	Photoelectrical reflection
Voltage monitoring	Yes





Art.-Nr. FURM80000 Seite 3 von 3

Technical data - Comfion wireless smoke alarm

Width 86 mm