

KLZS714 for fire doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



FOR FIRE DOORS

With this door fitting you secure fire doors against burglars.

A security risk from doors: The door cylinder often protrudes slightly. Burglars can use this weak point to gain unauthorised access. Your fire doors may also have this shortcoming. Therefore, protect them with a reliable door fitting. This door hardware was specially designed for mounting on fire doors with a door thickness of 37 to 47 millimetres. Several steel plates and extra long steel cams provide stability. A steel insert in the shield provides a high level of protection against tearing. The handle plate of the door fitting is equipped with a steel core and can be adjusted to right- and left-opening doors. The product is VdS and DIN certified and MPA monitored.

Technologies

- Certified according to DIN EN 1906 SK2 and DIN 18 257 ES1, VdS approved, supervised by the MPA NRW (German institute for testing of materials)
- Steel core in handle
- Maximum resistance due to the layer construction: several bottom plates for maximum protection
- High impact resistance: extra long steel cams, complete with tempered special screws (3 x M6)
- An additional steel inset provides extra strong leverage/tear-off resistance
- Integrated pulling protection with cylinder cover plus freely rotating special steel disk
- Grip plate adjustable to DIN left and right doors
- Spacing: 72 mm, square bolt: 9 mm
- U-lever shape

KLZS714 for fire doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

Operation and use

- For fire doors
- Suitable for rebated and flush doors, left and right opening
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm

Variants

- Finish: F1 (alu anodized)
- Alternatively available as a handle/handle set

Technical data - KLZS714 for fire doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	10-18 mm
Door fitting for fire doors	Yes
Door type	Fire door
Interchangeable fitting	Yes
Security Level Home Security	8
Weight	1680 g
colour	F1: Aluminum Nature
pulling protection	Yes
EAN	4003318425585