

EasyLook pan/tilt camera

Art.-Nr. PPDF17620X

Seite 1 von 2

Technical data - EasyLook pan/tilt camera

| | |
|-------------------------------|--|
| Area of application | Outdoor use |
| Base event | Software + Motion Mask |
| Channel width | 20 MHz |
| Colour | Black |
| Compatible with | PPDF17000; PPDF17100 |
| Compatible with Secoris | No |
| Compatible with Secvest | No |
| Compatible with Smartvest | No |
| Compatible with wAppLoxx | No |
| DC voltage supply | 12 V |
| Day/night switching | Auto |
| Dimensions | 210 x 120 x 160 mm |
| Encryption | WPA2 |
| Focal length | 4,1 mm |
| Frequency range | 2,403 - 2,478 GHz |
| Functions | Night vision, Zoom, Intercom (2-way audio), People recognition |
| Horizontal viewing angle | 85 ° |
| Housing material | Plastic |
| IP protection class | 66 |
| IR LEDs | Yes |
| IR range (up to) | 15 m |
| Image sensor | 1/3" CMOS |
| Loudspeaker | Yes |
| Max. humidity | 90 % |
| Max. operating temperature | 50 °C |
| Max. resolution @ frame rate | 2304 x 1296 @15fps |
| Microphone | Yes |
| Min. humidity | 30 |
| Min. operating temperature | -10 °C |
| Minimum illumination (IR) | 0,1 lx |
| Minimum illumination (colour) | 1 lx |
| Net weight | 0,687 kg |
| Optical Wave Length | 940 nm |
| Pan/tilt range | 270° / 90° |
| Plug type | DC-plug: 5,5 x 2,0 mm |
| Power consumption | 3,75 W |
| Power supply | Power adapter |

EasyLook pan/tilt camera

Art.-Nr. PPDF17620X

Seite 2 von 2

Technical data - EasyLook pan/tilt camera

| | |
|------------------------|---------------------------------------|
| Private zones | 4 |
| Resolution modes | 2304 x 1296 (3MP) |
| Sensitivity | -88 dBm |
| System | Stand-alone |
| Technology | Wireless |
| Transmission power | 20 dBm |
| Vertical viewing angle | 45 ° |
| Video bit rate | 2Mbps |
| Video compression | H.264+ |
| White balance | Auto |
| Wireless range | (Depending on installation) 20 - 50 m |