

Secvest Wireless Control Device

Art.-Nr. FUBE50001

Seite 1 von 3



Easy operation via code or proximity keyfob

The Secvest wireless control panel is an optional Secvest accessory. Every wireless control panel can be operated from your system via PIN code. It is possible to arm and disarm the panel via proximity keyfob.

Flexible use in entrance areas

Up to 8 control panels can be integrated into the alarm system. These additional modules can be placed in various areas of the building. This provides added convenience for you, because Secvest can be armed and disarmed directly on the wireless control panel, without the need to go back to the central alarm panel every time.

In addition to internal arming or arming individual sub-areas, you can also switch a single output, such as the garage door, if desired.

Secure wireless communication

Thanks to a secure wireless communication procedure, this product is protected against 'replay attacks', as are the Secvest wireless alarm system and Secvest Touch alarm systems. This procedure for preventing third party tampering exceeds the requirements of the "DIN EN 50131-1 level 2" security standard.

Technologies

- For arming/disarming the alarm panel
- Integrated proximity chip key reader
- Switching outputs possible
- Power supply using batteries and/or external power supply
- LEDs for displaying the current status
- Communicates with the Secvest and Secvest Touch via a secure wireless connection

Secvest Wireless Control Device

Art.-Nr. FUBE50001

Seite 2 von 3

Technical data - Secvest Wireless Control Device

AC voltage supply	9-12 V
Battery - max. battery life	1 y
Battery - type	3 x AA (1,5 V Alkaline)
Certifications	EN 50131 Grade 2, VdS home, VSÖ
Colour	white
DC voltage supply	9-15 V
Depth	30 mm
Dimensions	(WxHxD) 120x120x30 mm
EN	Grade 2
Environmental class	II
Height	120 mm
Housing material	ABS
IP protection class	54
Installation location	Indoors
Language of instructions	DE; EN; FR; NL; DK; IT
Length	30 mm
Max. humidity	94 %
Max. operating temperature	55 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	100 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,176 kg
PSTI conformity required	No
Power consumption	100 mA
Radio frequency	868,6625 MHz
Radio power	10 mW
Sabotage monitoring	Yes
Security level	2
Software version	2.9
Sound pressure	103,7 dB
Status display	Yes
VdS approval no.	H 115013

Secvest Wireless Control Device

Art.-Nr. FUBE50001

Seite 3 von 3

Technical data - Secvest Wireless Control Device

Voltage monitoring	Yes
Width	120 mm