

# 19.5" Full HD LED Monitor

Art.-Nr. TVAC10032

Seite 1 von 2



The 19.5" full HD LED monitor offers sharp images in 16:9 format and is ideal for surveillance projects with an ABUS recorder. High-resolution images are provided via an HDMI cable for precision monitoring.

#### Detailed surveillance pictures in full HD

Thanks to a rapid reaction time of just 5 ms, surveillance pictures are transmitted in a matter of seconds. Quick movements on the screen are shown clearly and continuously, without any distortions, flickering or ghost images. You see meaningful, reliable pictures in full HD quality.

#### Versatile connections

The video monitor can be connected to a recorder or PC. Thanks to the HDMI connection, the monitor is optimally suited to displaying images in full HD. An additional VGA and a DVI connection make the monitor a highly flexible component in a wide range of surveillance systems, and it is further equipped with an integrated loudspeaker and an audio input and output.

#### Energy efficiency for continuous monitoring

The efficient LED display ensures very low power consumption - ideal for continuous use.

#### Surveillance monitor for wall or ceiling

Fast mounting with VESA standard mounts: The monitor can be fixed to the wall or to the ceiling as per your requirements.

### Technologies

- Full HD resolution: 1920 x 1080 pixels
- Fast reaction time (5 ms) for flowing images
- LED backlighting: Brilliant colour display and high contrast

# 19.5" Full HD LED Monitor

Art.-Nr. TVAC10032

Seite 2 von 2

- Picture-in-picture display for more information at a glance
- Connections: HDMI, DVI, VGA, audio input and output
- Integrated loudspeakers
- Low power consumption for long-term monitoring (LED technology)
- Wall and ceiling installation possible (with VESA mount)

## Technical data - 19.5" Full HD LED Monitor

Brightness	250 cd/m <sup>2</sup>
Comb filter	3D
Connection type	1x VGA,1xDVI,1xHDMI, 1x Audio
Contrast ratio	1000:01
DC voltage supply	12 V
Depth	41 mm
Dimensions	(WxHxD) 470x360x45 mm
Display surface	matte
Gross weight	3,3 kg
Height	360 mm
Housing material	Plastic
Image format	16:09
Length	41 mm
Loudspeaker	2
Max. humidity	70 %
Max. operating temperature	50 °C
Min. operating temperature	0 °C
Monitor type	Standard TFT
Net weight	2,8 kg
OSD language	multilingual
PSTI conformity required	No
Power consumption	2.000 mA
Reaction time	5 ms
Screen diagonal	19,5 in
Signal detection	Automatic
Viewing angle horizontal/vertical	75/80
Width	470 mm