

Secvest Small Wireless Magnetic Contact (white)

Art.-Nr. FUMK50031W

Seite 1 von 2



Reliable alarm triggering in the event of intrusion

The wireless opening detector detects and reports the unauthorised opening of doors and windows using a magnetic contact. In such cases, it informs the wireless alarm panel, which then triggers a corresponding alarm.

For particularly small installation proportions

The wireless opening detector has a distinctive sleek design, making it particularly suitable for tight installation locations. The product consists of a detector and a magnet, which are mounted parallel to each other on the moving part of the window or door, and on the window or door frame. If the distance between the two contact points increases when the window or door is opened, the detector is triggered.

Technologies

- Sleek design, particularly suitable for tight installation locations
- Reliably detects opening of windows and doors
- Tamper monitoring

Technical data - Secvest Small Wireless Magnetic Contact (white)

Battery - max. battery life	2 y
Battery - quantity	1
Battery - type	CR2 3V Li/MnO ₂
Certifications	EN 50131 Grad 2
Colour	white
Colour options	white, brown
Compatible with	Secvest, Terxon, BUM060040
DC voltage supply	3 V
Dimensions	(WxHxD) 19x103x24 mm

Secvest Small Wireless Magnetic Contact (white)

Art.-Nr. FUMK50031W

Seite 2 von 2

Technical data - Secvest Small Wireless Magnetic Contact (white)

EN	Grade 2
Environmental class	II
Height	103 mm
Housing material	ABS
IP protection class	34
Installation location	Windows, doors
Language of instructions	DE; EN, FR, NL, DK, IT
Language packing	DE; EN, FR, NL, DK, IT
Length	24 mm
Max. operating temperature	55 °C
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,052 kg
PSTI conformity required	No
Radio frequency	868,6625 MHz
Radio power	10 mW
Sabotage monitoring	Yes
Security level	2
Sensor type	Reed contact
Status display	Yes
Type of detection	Magnetic field measurement
VdS class	none
Voltage monitoring	Yes
Width	19 mm